OUTLINE FOR SMALL PRINTING FACILITIES TO CALCULATE MAXIMUM THEORETICAL EMISSIONS FOR DETERMINING APPLICABILITY OF THE LITHOGRAPHIC PRINTING RULE

The following guide outlines one method for estimating a small facility's maximum theoretical emissions (MTE) to determine if the lithographic printing regulation applies. Facilities are not bound to this methodology; but it is one method that the Department will accept. This guide is not all inclusive and individual variations in printing operations may need to be considered. This guide may not be appropriate for determining MTE for other regulatory purposes, such as for permitting. All calculations do <u>not</u> include consideration of control devices, such as catalytic or thermal incinerators.

This guide is divided into three sections: non-heatset web presses, heatset web presses, and sheet-fed nonheatset presses. Complete the appropriate section for each individual press, then total the results from all the presses. This total is the Maximum Theoretical Emissions for your entire printing operation.

All of the calculations utilize the volatile organic compound (VOC) content of a material. Information about the VOC content, expressed as pounds VOC per gallon OR as percent VOC of an ink, coating, or solution can usually be found on the accompanying Material Safety Data Sheet (MSDS), through your distributor or supplier, or from the label on the container. In some cases where a solution is mixed on site, the VOC content of the solution may have to be calculated by hand. For this guide, it has been assumed that the VCC content of inks (also called coatings) is typically expresses as a percentage, and that the VCC content of solutions or washes are typically expressed as pounds VOC per gallon (lbs VOC/gal).

For determining the maximum usage of fountain solution or blanket/roller wash for one press, simply apply a ratio of (maximum ink usage)/(actual ink usage) to the actual usage of fountain solution or blanket/roller wash. Maximum ink usage should be calculated as outlined below. Actual usage of fountain solutions and blanket/roller washes can be determined from purchase records, or from other recordkeeping. If the fountain solutions or blanket/roller washes are in a closed, automated type system, then this method for determining actual usage may need to be modified.

Non-heatset Web Presses		
Maximum web width	in	(1)
Maximum ink coverage per print deck	lbs of ink/in ²	(2)
How many print decks?		(3)
Maximum line-speed	in/hr	(4)
Multiply (1)x(2)x(3)x(4)	lbs of ink/hr	(5)
Maximum VOC content ink	% VOC (by weight)	(6)
Multiply (0.05 x(5)x(6))/100	lbs VOC/hr	(7)
Multiply (7)x 730 hrs/mo *	lbs VOC/mo	(8)
Maximum fountain solution usage per month	gal/mo	(9)
Maximum VOC content	lbs VOC/gal	(10)
Multiply (9)X(10)	lbs VOC/mo	(11)
Maximum blanket/roller wash usage per month	gal/mo	(12)
Maximum VOC content	lbs VOC/gal	(13)
Multiply (12)x(13)	lbs VOC/mo	(14)
Add (8)+(11)+(14) * [Note: 24 hrs/day x 365 days/yr 12 mo/yr = 730 hrs/mo.]	lbs VOC/mo MTE	(15)
Heatset Web Presses		
Maximum web width	in	(1)
Maximum ink coverage per print deck	lbs of ink/in ²	(2)
How many print decks?		(3)
Maximum line-speed	in/hr	(4)
Multiply (1)x(2)x(3)x(4)	lbs of ink/hr	(5)
Maximum VOC content ink	% VOC (by weight)	(6)
Multiply (0.80 x(5)x(6))/100	lbs VOC/hr	(7)
Multiply (7)x 730 hrs/mo*	lbs VOC/mo	(8)
Maximum fountain solution usage per month	gal/mo	(9)
Maximum VOC content	lbs VOC/gal	(10)
Multiply (9)X(10)	lbs VOC/mo	(11)

Maximum blanket/roller wash usage per month	gal/mo	(12)	
Maximum VOC content	lbs VOC/gal	(13)	
Multiply (12)x(13)	lbs VOC/mo	(14)	
Add (8)+(11)+(14)	lbs VOC/mo MTE	(15)	
* (Note: 24 hrs/day x 365 days/yr - 12 mo/yr = 730 hrs/mo.)	103 V OC/IIIO WITE	(13)	
(Note: 24 his/day x 303 days/yr - 12 hio/yr = 750 his/hio.)			
Sheet-fed Presses	in^2	(1)	
Maximum sheet size		(1)	
Maximum ink coverage per print deck	lbs of ink/in ²	(2)	
How many print decks? Maximum line-speed	in/hr	(3)	
Multiply (1)x(2)x(3)x(4)	lbs of ink/hr	(4) (5)	
Maximum VOC content ink	% VOC (by weight)	(6)	
Multiply (0.05 x(5)x(6))/100	lbs VOC/hr	` '	
Multiply (7)x 730 hrs/mo *	lbs VOC/mo	(7)	
Multiply (7)x 750 Hrs/mo *	los VOC/IIIo	(8)	
Maximum fountain solution usage per month	gal/mo	(9)	
Maximum VOC content	lbs VOC/gal	(10)	
Multiply (9)X(10)	lbs VOC/mo	(11)	
Maximum blanket/roller wash usage per month	gal/mo	(12)	
Maximum VOC content	lbs VOC/gal	(13)	
Multiply (12)x(13)	lbs VOC/mo	(14)	
Add (8)+(11)+(14)	lbs VOC/mo MTE	(15)	
* (Note: 24 hrs/day x 365 days/yr - 12 mo/yr = 730 hrs/mo.)			
EXAMPLE (1 facility with 5 presses)			
Press #1: Sheet-fed Press			
Maximum sheet size	864 in ²	(1)	
Maximum ink coverage per print deck	0.000032 lbs of ink/in ²	(2)	
How many print decks? Maximum line-speed	6 20 sheets/hr	(3) (4)	
Multiply (1)x(2)x(3)x(4)	$= \frac{20}{3.32} \frac{\text{sheets/in}}{\text{lbs of ink/hr}}$	(5)	
Maximum VOC content ink	30 % VOC (by wgt.)	(6)	
Multiply (0.05 x(5)x(6))/100	$= \frac{0.05}{\text{lbs VOC/hr}}$	(7)	
Multiply (7)x 730 hrs/mo	= 36 lbs VOC/mo	(8)	
Maximum fountain solution usage per month	12gal/mo	(9)	
Maximum VOC content	6.7 lbs VOC/gal	(10)	
Multiply (9)X(10)	= <u>80</u> lbs VOC/mo	(11)	
Maximum blanket/roller wash usage per month	20 gal/mo	(12)	
Maximum VOC content	7.36 lbs VOC/gal	(13)	
Multiply (12)x(13)	= <u>147</u> lbs VOC/mo	(14)	
Add (8)+(11)+(14) = 36 + 80 + 147	= <u>263</u> lbs VOC/mo MTE	(15)	
FACILITY SUMMARY:			
Press #1 Sheet-fed Non-heatset	263		
Press #2 Sheet-fed Non-heatset	220		
Press #3 Sheet-fed Non-heatset Press #4 Non-heatset	250 550		
Press #4 Non-heatset	625		
TOTAL FACILITY MTE	= 1908 lbs VOC/mo MTE for	facility	